

## Safety Data Sheet

Revision Date: 3/4/2020

M20 - Inspiration Fabric Coating

**Section 1. Product and Company Identification****Product Identifier** M200 - Inspiration Coating Fabric Protectant**Coating Product Use****Description:** Clear thin liquid for use as a fabric stain guard with menthol odor**Suppliers' details**CarCareCo Pty Ltd  
1/10 Access Way  
Carrum Downs VIC 3201**Emergency Number:** 131126  
**Customer Service: Business:** 1300 323 150**Section 2. Hazards Identification****GHS Classification****Flammable Liquids:** Category 2**GHS Label Elements****Hazard Pictograms****Hazard Word****Danger****Hazard Statements****H225: Highly flammable liquid and vapour****Precautionary Statements**

- P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking**
- P233: Keep container tightly closed**
- P240: Ground/bond container and receiving equipment**
- P242: Use only non-sparking tools**
- P243: Take precautionary measures against static discharge**
- P261: Avoid breathing dust/fume/gas/mist/vapours/spray**
- P271: Use only outdoors or in a well-ventilated area**
- P280: Wear protective gloves/protective clothing/eye protection/face protection**
- P303: IF ON SKIN (or hair):**
- P361: Remove/Take off immediately all contaminated clothing**
- P353: Rinse skin with water/shower**
- P370: IN CASE OF FIRE:**
- P378: Use dry sand, dry chemical or alcohol resistant foam for extinction.**
- P403: Store in a well ventilated place**
- P233: Keep container tightly closed**
- P235: Keep cool**
- P501: Dispose of contents/container to an approved waste disposal plant.**

**Safety Data Sheet**

Revision Date: 3/4/2020

M20 - Inspiration Fabric Coating

**3. Composition Information on Ingredients**

CAS Number	Wt %	Component Name
540-88-5	4-7%	t-Butyl Acetate
541-02-6	60-70%	Decamethylcyclopenasiloxane

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

**4. First Aid Measures****Eye Contact:**

If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call a physician.

**Skin Contact:**

In case of skin contact, remove any contaminated clothing and wash skin with soap and water. Launder or dry-clean clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

**Inhalation:**

If overcome by vapor, remove victim to fresh air and call a physician immediately. If breathing is irregular or has stopped, start resuscitation, administer oxygen, if available.

**Ingestion:**

If ingested, DO NOT induce vomiting; call a physician immediately.

**5. Fire Fighting Measures****EXTINGUISHING MEDIA AND FIRE FIGHTING PROCEDURES**

Foam, water spray (fog), dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable for extinguishing fires involving this type of product, depending on size or potential size of fire and circumstances related to the situation. Plan fire protection and response strategy through consultation with local fire protection authorities or appropriate specialists.

Use dry chemical, foam or carbon dioxide to extinguish the fire. "Water may be ineffective", but water should be used to keep fire-exposed containers cool. If a leak or spill has ignited, use water spray to disperse the vapors and to protect persons attempting to stop a leak. Water spray may be used to flush spills away from exposures. Minimize breathing of gases, vapor, fumes or decomposition products. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

**DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS**

Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other decomposition products, in the case of incomplete combustion.

**6. Accidental Release Measures****CLEAN WATER ACT / OIL POLLUTION ACT**

This product may be classified as an oil under Section 311 of the Clean Water Act, and under the Oil Pollution Act. Discharges or spills into or leading to surface waters that cause a sheen must be reported to the National Response Center (1-800-424-8802).

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Shut off and eliminate all ignition sources. Keep people away. Recover free product. Add sand, earth

## Safety Data Sheet

Revision Date: 3/4/2020

M20 - Inspiration Fabric Coating

or other suitable absorbent to spill area. Minimize breathing vapors. Minimize skin contact. Ventilate confined spaces. Open all windows and doors. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses, or extensive land areas.

Assure conformity with applicable governmental regulations. Continue to observe precautions for volatile, combustible vapors from absorbed material.

## 7. Handling and Storage

### HANDLING PRECAUTIONS

This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

Keep product away from ignition sources, such as heat, sparks, pilot lights, static electricity, and open flames.

## 8. Exposure Controls and Personal Protection

540-88-5	t-Butyl Acetate	200 ppm (OSHA) PEL (8 hr TWA)
		200 ppm (ACGIH) TLV (8 hr TWA)
541-02-6	Decamethylcyclopenasiloxane	N/A

### Ventilation:

Use only with ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air. No smoking or use of flame or other ignition sources.

### Respiratory Protection:

If the exposure limit is exceeded and engineering controls are not feasible, wear a supplied air, full-facepiece respirator, air-lined hood, or full-facepiece self-contained breathing apparatus. Breathing air quality must meet the requirements of the OSHA respiratory protection standard (29CFR1910.134).

### Protective Gloves:

Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

### Eye Protection:

Use splash goggles or face shield when eye contact may occur.

### Work Practices:

To prevent fire or explosion risk from static accumulation and discharge, effectively bond and/or ground product transfer system in accordance with (THE) National Fire Protection Association PUBLICATIONS.

## 9. Physical and Chemical Properties

Flash Point	4°C (39°F) TCC	Upper Flammability Limit	1.7 %
Auto Ignition	224°C (435°F)	Lower Flammability Limit	1.5 %
Physical State	Liquid	Color	Clear/colorless
pH	NA	Vapor Press	42 mmHg
	Specific Gravity .93	Viscosity	

## Safety Data Sheet

Revision Date: 3/4/2020

M20 - Inspiration Fabric Coating

<b>Vapor Density (Air=1)</b> > 1.0	<b>Melting Point °F</b> unknown	<b>Odor</b> menthol
<b>Water Solubility</b> very low	<b>VOC Content</b> 18.4%, 0.53 lb/gal	CARB Exempt and LVP Solvents

### 10. Stability and Reactivity

**Stability** Stable

**Hazardous Polymerization** Not Expected to Occur

**Conditions to Avoid**

Keep away from extreme heat, Strong Acids, Alkalis and Oxidizers such as Chlorine, other Halogens, Hydrogen Peroxide and Oxygen

**Hazardous Decomposition Products** No substances are readily identifiable from composition but no degradation data is available.

### 11. Toxicological Information

t-Butyl Acetate

LD50 &gt; 4100 mg/kg (oral - male rat)

LD50 &gt; 2000 mg/kg (male and female rabbit)

Not a skin sensitizer or carcinogenic hazard

### 12. Ecological Information

t-Butyl Acetate

LC50 = 240 mg/l (96 hour, OECD 203, Rainbow Trout) semi static

EC50 = 350 mg/l (48 hour, Daphnia magna, OECD 202)

### 13. Disposal Considerations

Options for disposal of this product may depend on the conditions under which it was used. To determine the proper method of disposal, refer to RCRA (40 CFR 261), as well as federal EPA and state and local regulations.

Please refer to Sections 5, 6 and 15 for additional information.

### 14. Transportation Information

Combination package, inner package under 1 Liter

Not Considered Hazardous, exception 173.150(b)(2)

Non-bulk packaging (capacity greater than or equal to 1 Liter)

UN1993, Flammable Liquid, N.O.S. (Butyl Acetates), 3, PG II

Transported by air or marine vessel:

Bulk or non-bulk packaging

UN1993, Flammable Liquid, N.O.S. (Butyl Acetates), 3, PG II

### 15. Regulatory Information

TSCA - Inventory Status All Items on TSCA Inventory

**Safety Data Sheet**

Revision Date: 3/4/2020

M20 - Inspiration Fabric Coating

TSCA 12(B) - ACC#255846 Fluorinated acrylic copolymer (subject to export notification) SARA 311/312 - Fire  
SARA 313 - None  
SARA 302 - None  
CA Prop 65 - Contains no known hazardous materials above the safe harbor limits

**16. Other Information****Revision Date** 3/4/2020

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to ensure proper health, safety and other necessary information is included on the container.

**Key or legend to abbreviations and acronyms used in the safety data sheet**

ACGIH American Conference of Government Industrial Hygienists

LD50 Lethal Dose 50%

AICS Australia, Inventory of Chemical Substances

LOAEL Lowest Observed Adverse Effect Level

DSL Canada, Domestic Substances List

NFPA National Fire Protection Agency

NDSL Canada, Non-Domestic Substances List

NIOSH National Institute for Occupational Safety &amp; Health

CNS Central Nervous System

NTP National Toxicology Program

CAS Chemical Abstract Service

NZIoC New Zealand Inventory of Chemicals

EC50 Effective Concentration

NOAEL No Observable Adverse Effect Level

EC50 Effective Concentration 50%

NOEC No Observed Effect Concentration

EGEST EOSCA Generic Exposure Scenario Tool

OSHA Occupational Safety &amp; Health Administration

EOSCA European Oilfield Specialty Chemicals Association

PEL Permissible Exposure Limit

EINECS European Inventory of Existing Chemical Substances

PICCS Philippines Inventory of Commercial Chemical Substances

MAK Germany Maximum Concentration Values

PRNT Presumed Not Toxic

GHS Globally Harmonized System

RCRA Resource Conservation Recovery Act

&gt;= Greater Than or Equal to STEL

Short-term Exposure Limit IC50

Inhibition Concentration 50%

SARA Superfund Amendments and Reauthorization Act.

IARC International Agency for Research on Cancer TLV

Threshold Limit Value

## Safety Data Sheet

Revision Date: 3/4/2020

M20 - Inspiration Fabric Coating

---

IECSC Inventory of Existing Chemical Substances in China

TWA Time Weighted Average

ENCS Japan, Inventory of Existing and New Chemical Substances

TSCA Toxic Substance Control Act

KECI Korea, Existing Chemical Inventory

UVCB Unknown or Variable Composition, Complex Reaction Products, and Biological Materials

<= Less Than or Equal To

WHMIS Workplace Hazardous Materials Information System

LC50 Lethal Concentration 50%



**P & S Sales, Inc.**

**Safety Data Sheet**

M20 - Inspiration Fabric Coating

Page 7

Revision Date: 3/4/2020

---



**P & S Sales, Inc.**

**Safety Data Sheet**

M20 - Inspiration Fabric Coating

Page 8

Revision Date: 3/4/2020

---





**P & S Sales, Inc.**

**Safety Data Sheet**

M20 - Inspiration Fabric Coating

Page 9

Revision Date: 3/4/2020

---



**P & S Sales, Inc.**

**Safety Data Sheet**

M20 - Inspiration Fabric Coating

Page 10

Revision Date: 3/4/2020

---



**P & S Sales, Inc.**

**Safety Data Sheet**

M20 - Inspiration Fabric Coating

Page 11

Revision Date: 3/4/2020

---