

Safety Data Sheet

Revision Date: 27/5/2020

RT12 - Metal Bright

Section 1. Product and Company Identification

Product Identifier RT12 - Metal Bright

Product Use

Description: White lotion with solvent peppermint odor for use as a Metal Polish

Suppliers' details

CarCareCo Pty Ltd
1/10 Access Way
Carrum Downs VIC 3201

Emergency Number: 131126
Customer Service: 1300 323 150

Section 2. Hazards Identification

GHS Classification

Flammable Liquids: Category 4

Skin Irritation : Category 2

Eye Irritation : Category 2A

Specific target organ toxicity - single exposure: Category 3 (Central nervous system)

Aspiration Hazard: Category 1

GHS Label Elements

Hazard pictograms



Hazard Word

Danger

Hazard Statements

Combustible liquid

May be fatal if swallowed and enters airways

Causes skin irritation

Causes serious eye irritation

May cause drowsiness or dizziness

Safety Data Sheet

Revision Date: 27/5/2020

RT12 - Metal Bright

Precautionary Statements**Keep away from heat/sparks/open flames/hot surfaces – No smoking****Avoid breathing dust/fume/gas/mist/vapours/spray****Use only outdoors or in a well-ventilated area****Wear protective gloves/protective clothing/eye protection/face protection****IF SWALLOWED:****Immediately call a POISON CENTER or doctor/physician****IF ON SKIN:****Wash with soap and water****IF INHALED:****Remove victim to fresh air and keep at rest in a position comfortable for breathing****Call a POISON CENTER or doctor/physician if you feel unwell****IF IN EYES:****Rinse cautiously with water for several minutes****Remove contact lenses if present and easy to do. continue rinsing****Do NOT induce vomiting****IN CASE OF FIRE:****Use dry sand, dry chemical or alcohol resistant foam for extinction.****Store in a well ventilated place****Keep container tightly closed****Store locked up****Dispose of contents/container to an approved waste disposal plant.****3. Composition Information on Ingredients**

CAS Number	Wt %	Component Name
64742-47-8	50-90%	Distillates (petroleum), hydrotreated light
64742-96-7	50-90%	Solvent Naphtha (petroleum), medium aliphatic

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

4. First Aid Measures**EYE CONTACT**

If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call a physician.

SKIN

In case of skin contact, remove any contaminated clothing and wash skin with soap and water. Launder or dry-clean clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

Safety Data Sheet**RT12 - Metal Bright****INHALATION**

If overcome by vapor, remove from exposure and call a physician immediately. If breathing is irregular or has stopped, start resuscitation, administer oxygen, if available.

INGESTION

If ingested, DO NOT induce vomiting; call a physician immediately.

5. Fire Fighting Measures**EXTINGUISHING MEDIA AND FIRE FIGHTING PROCEDURES**

Foam, water spray (fog), dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable for extinguishing fires involving this type of product, depending on size or potential size of fire and circumstances related to the situation. Plan fire protection and response strategy through consultation with local fire protection authorities or appropriate specialists.

Use dry chemical, foam or carbon dioxide to extinguish the fire. "Water may be ineffective", but water should be used to keep fire-exposed containers cool. If a leak or spill has ignited, use water spray to disperse the vapors and to protect persons attempting to stop a leak. Water spray may be used to flush spills away from exposures. Minimize breathing of gases, vapor, fumes or decomposition products. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS

Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other decomposition products, in the case of incomplete combustion.

6. Accidental Release Measures**CLEAN WATER ACT / OIL POLLUTION ACT**

This product may be classified as an oil under Section 311 of the Clean Water Act, and under the Oil Pollution Act. Discharges or spills into or leading to surface waters that cause a sheen must be reported to the National Response Center (1-800-424-8802).

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Shut off and eliminate all ignition sources. Keep people away. Recover free product. Add sand, earth or other suitable absorbent to spill area. Minimize breathing vapors. Minimize skin contact. Ventilate confined spaces. Open all windows and doors. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses, or extensive land areas.

Assure conformity with applicable governmental regulations. Continue to observe precautions for volatile, combustible vapors from absorbed material.

7. Handling and Storage**HANDLING PRECAUTIONS**

This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

Keep product away from ignition sources, such as heat, sparks, pilot lights, static electricity, and open flames.

Safety Data Sheet

Revision Date: 27/5/2020

RT12 - Metal Bright

8. Exposure Controls and Personal Protection

64742-47-8	Distillates (petroleum), hydrotreated light	400 ppm, 1600 mg/m3 (OSHA PO) TWA 500 ppm, 2000 mg.m3 (OSHA PEL 8 hour) TWA 200 mg/m3 (as total hydrocarbon vapor) ACGIH
64742-96-7	Solvent Naphtha (petroleum), medium aliphatic	400 ppm, 1600 mg/m3 (OSHA PO) TWA 500 ppm, 2000 mg.m3 (OSHA PEL 8 hour) TWA 200 mg/m3 (as total hydrocarbon vapor) ACGIH

VENTILATION

Use only with ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air. No smoking or use of flame or other ignition sources.

RESPIRATORY PROTECTION

Use supplied-air respiratory protection in confined or enclosed spaces, if needed.

PROTECTIVE GLOVES

Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

EYE PROTECTION

Use splash goggles or face shield when eye contact may occur.

OTHER PROTECTIVE EQUIPMENT

Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing, which could result in prolonged or repeated skin contact.

WORK PRACTICES / ENGINEERING CONTROLS

To prevent fire or explosion risk from static accumulation and discharge, effectively bond and/or ground product transfer system in accordance with (THE) National Fire Protection Association PUBLICATIONS.

9. Physical and Chemical Properties

Flash Point	89°C (192°F) TCC	Upper Flammability Limit	7.0%
Auto Ignition	215.5°C (420°F)	Lower Flammability Limit	0.6 %
Physical State	Liquid	Color	White, Opaque
pH	N/A	Vapor Press	1 mmHg
Specific Gravity	.82	Viscosity	Thin
Vapor Density (Air=1)	4.8	Melting Point °F	N/A
Water Solubility	Negligible	Odor	Peppermint/Solvent
		VOC Content	46%, See Section 15 for more details

Safety Data Sheet

Revision Date: 27/5/2020

RT12 - Metal Bright

10. Stability and Reactivity

Stability Stable**Hazardous Polymerization** Not Expected to Occur**Conditions to Avoid**

Keep away from extreme heat, Strong Acids, Alkalis and Oxidizers such as Chlorine, other Halogens, Hydrogen Peroxide and Oxygen

**Hazardous
Decomposition Products**

No substances are readily identifiable from composition but no degradation data is available.

11. Toxicological Information

NATURE OF HAZARD AND TOXICITY INFORMATION

Prolonged or repeated skin contact with this product tends to remove skin oils, possibly leading to irritation and dermatitis; however, based on human experience and available toxicological data, this product is judged to be neither a "corrosive" nor an "irritant" by OSHA criteria.

This product is judged to have an acute oral LD50 (rat) greater than 5 g/kg of body weight, and an acute dermal LD50 (rabbit) greater than 3.16 g/kg of body weight.

12. Ecological Information

Do not discharge this product into public waters or waterways unless authorized by a National Pollution Discharge Elimination System (NPDES) permit issued by the Environmental Protection Agency (EPA).

13. Disposal Considerations

Options for disposal of this product may depend on the conditions under which it was used. To determine the proper method of disposal, refer to RCRA (40 CFR 261), as well as federal EPA and state and local regulations.

Please refer to Sections 5, 6 and 15 for additional information.

14. Transportation Information

Domestic Transportation, not by air:

Non-bulk packaging (capacity less than or equal to 119 gallons) Not regulated

Transported by marine vessel:

Bulk packages (capacity greater than 119 Gallons)

UN1993, Flammable Liquid, N.O.S. (Naphtha Solvent), 3, PG III

Non-bulk packaging (capacity less than or equal to 1.3 gallons)

Limited Quantity exception: 49 CFR 173.150(b)(3) Packaging under 5 Liter or 1.3 Gallons

Not Regulated

15. Regulatory Information

Safety Data Sheet

Revision Date: 27/5/2020

RT12 - Metal Bright

OSHA Hazards: Combustible Liquid, Moderate skin Irritant, Moderate Eye Irritant

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity - This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards: Fire hazard, Acute Health Hazard

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313: **SARA 313:** This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65: This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

Clean Air Act (CAA) -

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489)

Clean Water Act -

This product does not contain any Hazardous Substances listed under the U.S. Clean Water Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. Clean- Water Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

CARB VOC info: 0% VOC as regulated by CARB Consumer Products requirements, LVP-VOC exception

ARB VOC Info: 4.1 lb/gal VOC; 469 g/L

16. Other Information

Revision Date 27/5/2020

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to ensure proper health, safety and other necessary information is included on the container.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH American Conference of Government Industrial Hygienists

Safety Data Sheet**RT12 - Metal Bright**

LD50 Lethal Dose 50%
AICS Australia, Inventory of Chemical Substances
LOAEL Lowest Observed Adverse Effect Level
DSL Canada, Domestic Substances List
NFPA National Fire Protection Agency
NDSL Canada, Non-Domestic Substances List
NIOSH National Institute for Occupational Safety & Health
CNS Central Nervous System
NTP National Toxicology Program
CAS Chemical Abstract Service
NZIoC New Zealand Inventory of Chemicals
EC50 Effective Concentration
NOAEL No Observable Adverse Effect Level
EC50 Effective Concentration 50%
NOEC No Observed Effect Concentration
EGEST EOSCA Generic Exposure Scenario Tool
OSHA Occupational Safety & Health Administration
EOSCA European Oilfield Specialty Chemicals Association
PEL Permissible Exposure Limit
EINECS European Inventory of Existing Chemical Substances
PICCS Philippines Inventory of Commercial Chemical Substances
MAK Germany Maximum Concentration Values
PRNT Presumed Not Toxic
GHS Globally Harmonized System
RCRA Resource Conservation Recovery Act
>= Greater Than or Equal to STEL
Short-term Exposure Limit IC50
Inhibition Concentration 50%
SARA Superfund Amendments and Reauthorization Act.
IARC International Agency for Research on Cancer TLV
Threshold Limit Value
IECSC Inventory of Existing Chemical Substances in China
TWA Time Weighted Average
ENCS Japan, Inventory of Existing and New Chemical Substances
TSCA Toxic Substance Control Act
KECI Korea, Existing Chemical Inventory
UVCB Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<= Less Than or Equal To
WHMIS Workplace Hazardous Materials Information System
LC50 Lethal Concentration 50%