P&S Sales, Inc.

Safety Data Sheet

C29 - Inspiration SOLE Coating

Section 1. Product and Company Identification

Product Identifier C29 - Inspiration SOLE Coating

Product Use Description:

Thin clear liquid with solvent and amine odors for use as a clear coating on automotive finishes.

Manufacturer or suppliers' details

P & S Sales, Inc 20943 Cabot Blvd. Hayward CA 94545

Emergency Number:	800-255-3924
Customer Service:	510-732-2628
Business Fax:	510-732-2632

Section 2. Hazards Identification

GHS Classification

Flammable Liquids : Category 3 Skin Corrosion/Irritation : Category 2

- Eye Damage : Category 2
- **Reproductive Toxicity** : Category 2
 - **Aspiration Hazard** : Category 1

GHS Label Elements

Hazard Pictograms



Hazard Word

Danger

Hazard Statements

Causes skin irritation Causes serious eye irritation Suspected of damaging fertility May be fatal if swallowed and enters airways Flammable liquid and vapour Harmful if swallowed Very toxic to aquatic life with long lasting effects

Precautionary Statements

- P201: Obtain special instructions before use
- P202: Do not handle until all safety precautions have been read and understood
- P210: Keep away from heat/sparks/open flames/hot surfaces No smoking
- P233: Keep container tightly closed
- P240: Ground/bond container and receiving equipment
- P241: Use explosion-proof electrical/ventilating/light/.../equipment
- P242: Use only non-sparking tools
- P243: Take precautionary measures against static discharge



Revision Date: 10/12/2020



P&S Sales, Inc. Safety Data Sheet

C29 - Inspiration SOLE Coating

- P264: Wash skin thoroughly after handling
- P270: Do not eat, drink or smoke when using this product
- P280: Wear protective gloves/protective clothing/eye protection/face protection
- P301+312: Response:
- P303+361+353: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
 - P308+313: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse P331: skin with water/shower
 - P332+313: IF exposed or concerned: Get medical advice/attention
 - P337+313: Do NOT induce vomiting
 - P362: If skin irritation occurs: Get medical advice/attention
 - P370: If eye irritation persists: Get medical advice/attention
 - P378: Take off contaminated clothing and wash before reuse
 - P403: IN CASE OF FIRE:
 - P405: Use dry sand, dry chemical or alcohol resistant foam for extinction.
 - P501: Store in a well ventilated place
 - Store locked up Dispose of contents/container to an approved waste disposal plant.

3. Composition Information on Ingredients

CAS Number	Wt %	Component Name
541-02-6 475645-84-2 556-67-2 64742-47-8	12-20% 1-3% 55-70% 12-20%	decamethylcyclopentasiloxane poly siloxane octamethylcyclotetrasiloxane Distillate (petroleum) Hydrotreated light
67-56-1	.1-<1%	methanol

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

4. First Aid Measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

Provide fresh air.

Following skin contact

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.

Following eye contact

Irrigate copiously with clean, fresh water, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

5. Fire Fighting Measures



Safety Data Sheet

C29 - Inspiration SOLE Coating

P&S Sales, Inc.

Revision Date: 10/12/2020

FLAMMABLE OR EXPLOSIVE LIMITS (APPROXIMATE PERCENT BY VOLUME IN AIR) Estimated values: Lower Flammable Limit 1.9% Upper Flammable Limit 12.6%

EXTINGUISHING MEDIA AND FIRE FIGHTING PROCEDURES

Foam, water spray (fog), dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable for extinguishing fires involving this type of product, depending on size or potential size of fire and circumstances related to the situation. Plan fire protection and response strategy through consultation with local fire protection authorities or appropriate specialists.

Use dry chemical, foam or carbon dioxide to extinguish the fire. "Water may be ineffective", but water should be used to keep fire-exposed containers cool. If a leak or spill has ignited, use water spray to disperse the vapors and to protect persons attempting to stop a leak. Water spray may be used to flush spills away from exposures. Minimize breathing of gases, vapor, fumes or decomposition products. Use

supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS

Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other decomposition products, in the case of incomplete combustion.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up Advices on how to contain a spill Covering of drains.

Advices on how to clean up a spill Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage (sawdust, kieselgur (diatomite), sand, universal bind- er). Appropriate containment techniques Use of adsorbent materials. Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal precautions: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Revision Date: 10/12/2020



Safety Data Sheet

C29 - Inspiration SOLE Coating

P & S Sales, Inc.

7.1 Precautions for safe handling Recommendations

Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Warning

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air. Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equip- ment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in con-tainers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

8. Exposure Controls and Personal Protection

541-02-6 decamethylcyclopentasiloxane	301 mg/m3 ACGIH TWA Oral
475645-84-2 poly siloxane	
556-67-2 octamethylcyclotetrasiloxane	
64742-47-8 Distillate (petroleum) Hydrotreated light	••
67-56-1 methanol	200 ppm PEL 250 ppm STEL
	200 ppm REL. 250 ppm STEL

VENTILATION

Use only with ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air. No smoking, or use of flame or other ignition sources.

RESPIRATORY PROTECTION

Use supplied-air respiratory protection in confined or enclosed spaces, if needed.

PROTECTIVE GLOVES

Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

EYE PROTECTION

Use splash goggles or face shield when eye contact may occur.

OTHER PROTECTIVE EQUIPMENT

Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing, which could result in prolonged or repeated skin contact.

WORK PRACTICES / ENGINEERING CONTROLS

To prevent fire or explosion risk from static accumulation and discharge, effectively bond and/or ground product transfer system in accordance with (THE) National Fire Protection Association PUBLICATIONS.

9. Physical and Chemical Properties

Flash Point 46°C (115°F) TCC Auto Ignition 645°K (1162°F) Physical State Liquid

Upper Flamability Limit Not Determined Lower Flamability Limit Not Determined Vapor Press 132 Pa at 25°C Color Clear

P&S Sales, Inc.

Safety Data Sheet

C29 - Inspiration SOLE Coating

5

Revision Date: 10/12/2020

pH N/A	Specific Gravity .9	47	Viscosity Thin	
Vapor Density (A	i r=1) .97	Melting Point °F N/A	Odor Amine Solvent	
Water Solubility	Not Determined	VOC Content	4.3 lb/Gal, See section 15 for CARB info	
10. Stability and	Reactivity			
Stability Stable		Hazardous Polymeriza	tion Not Expected to Occur	

Conditions to Avoid

Keep away from extreme heat, Strong Acids, Alkalies and Oxidizers such as Chlorine, other Halogens, Hydrogen Peroxide and Oxygen

Hazardous No substances are readily identifiable from composition but no degradation data is available.

11. Toxicological Information

Test data are not available for the complete mixture. **Classification procedure** The method for classification of the mixture is based on ingredients of the mixture (additivity formula). Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200) Acute toxicity Harmful if swallowed. Acute toxicity estimate (ATE) Shal not be classified as acutely toxic Skin corrosion/irritation Causes skin irritation Serious eye damage/eye irritation Causes serious eye irritation Respiratory or skin sensitization Shall not be classified as a respiratory or skin sensitizer. Summary of evaluation of the CMR properties Suspected of damaging fertility. Shall not be classified as carcinogenic. Shall not be classified as germ cell mutagenic. Carcinogenicity • National Toxicology Program (United States): none of the ingredients are listed • IARC Monographs: none of the ingredients are listed Specific target organ toxicity (STOT) Shall not be classified as a specific target organ toxicant. Aspiration hazard May be fatal is swallowed and enters airways

12. Ecological Information

Octamethylcyclotetrasiloxane:

Toxicity to fish :LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.022 mg/l Exposure time: 96 h Remarks: No toxicity at the limit of solubility. Toxicity to daphnia and aquatic invertebrates: EC50(Daphnia sp.): > 0.015 mg/l Exposure time: 48 h Remarks: No toxicity at the limit of solubility. Toxicity to algae: EC50: > 0.022 mg/l Exposure time: 96 h Remarks: No toxicity at the limit of solubility. NOEC: 0.022 mg/l



P&S Sales, Inc.

Page

6



C29 - Inspiration SOLE Coating

Safety Data Sheet

Exposure time: 96 h

Remarks: No toxicity at the limit of solubility. Methanol: LC50 15,400 mg/L fish 96 hr, EC50 12,700 mg/L fish 96 hr Distillates (petroleum) hydrotreated, light: LL50 5 mg/L fish 96 hr, EL50 1.4 mg/L aquatic invertebrates 48 hr 13. Disposal Considerations

Options for disposal of this product may depend on the conditions under which it was used. To determine the proper method of disposal, refer to RCRA (40 CFR 261), as well as federal EPA and state and local regulations.

Do not empty into drains. Avoid release to the environment. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

14. Transportation Information

Domestic Transportation, not by air: Non-bulk packagings (capacity less than or equal to 119 gallons)

Not regulated - Reclassified as combustible 49 CFR 173.150(f)

Transported by marine vessel: as supplied

Non-bulk packagings (capacity less than or equal to 119 gallons)

Not regulated - Reclassified as combustible 49 CFR 173.150(f)

Transportation by Air IATA: as supplied

Limited Quantity exception: 49 CFR 173.150(b)(3), 173.27 table 3 - Combination packaging under 2.5 Liter or .65 gallon per inner container and less than 10 liters per box - <u>Not Regulated</u> **Not as supplied**

Packaging greater than 2.5 Liter or .65 Gallon per inner container or more than 10 liters per box UN1993, Flammable Liquid n.o.s., 3, PGIII

15. Regulatory Information

OSHA Hazards : Combustible Liquid, Moderate skin Irritant, Chronic Health Hazard

EPCRA - Emergency Planning and Community Right-to-Know - none of the ingredients are listed

CERCLA Reportable Quantity - This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313: SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65 : No ingredients listed

Revision Date: 10/12/2020



Safety Data Sheet

C29 - Inspiration SOLE Coating

16. Other Information

10/12/2020 **Revision Date**

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH American Conference of Government Industrial Hygienists LD50 Lethal Dose 50% AICS Australia, Inventory of Chemical Substances LOAEL Lowest Observed Adverse Effect Level DSL Canada, Domestic Sub- stances List NFPA National Fire Protection Agency NDSL Canada, Non-Domestic Sub- stances List NIOSH National Institute for Occupational Safety & Health CNS Central Nervous System NTP National Toxicology Program CAS Chemical Abstract Service NZIoC New Zealand Inventory of Chemicals EC50 Effective Concentration NOAEL No Observable Adverse Effect Level EC50 Effective Concentration 50% NOEC No Observed Effect Concentration EGEST EOSCA Generic Exposure Scenario Tool OSHA Occupational Safety & Health Administration EOSCA European Oilfield Specialty Chemicals Association PEL Permissible Exposure Limit EINECS European Inventory of Exist- ing Chemical Substances PICCS Philipines Inventory of Commercial Chemical Substances MAK Germany Maximum Concentration Values PRNT Presumed Not Toxic GHS Globally Harmonized System RCRA Resource Conservation Recovery Act >= Greater Than or Equal To STEL Short-term Exposure Limit IC50 Inhibition Concentration 50% SARA Superfund Amendments and Reauthorization Act. IARC International Agency for Re- search on Cancer TLV Threshold Limit Value IECSC Inventory of Existing Chemical Substances in China TWA Time Weighted Average ENCS Japan, Inventory of Existing and New Chemical Sub- stances TSCA Toxic Substance Control Act KECI Korea, Existing Chemical Inventory UVCB Unknown or Variable Composition, Complex Reaction Products, and Biological Materials <= Less Than or Equal To WHMIS Workplace Hazardous Materials In- formation System LC50 Lethal Concentration 50%

P&S F C29

P & S Sales, Inc.Safety Data SheetC29 - Inspiration SOLE Coating

Page 8

Revision Date: 10/12/2020



P & S Sales, Inc.Safety Data SheetC29 - Inspiration SOLE Coating

Revision Date: 10/12/2020

P&S s

P & S Sales, Inc.Safety Data SheetC29 - Inspiration SOLE Coating

Page 10

Revision Date: 10/12/2020